

ibos[®]
SEWERAGE TECHNOLOGY



HD 260



A new generation of
a push rod camera with HD
image quality and axial
or rotary camera head

THE FUTURE IS IN DETAILS

IBOS a.s.
Hlínská 694/2b, 370 01 České Budějovice, Czech Republic
Tel.: +420 387 310 227, E-mail: ibos@ibos.cz



www.ibos.cz



HD 260

NEW

HD 260

- Push rod camera system with HD Box control panel
- Cable image transmission
- Designed for DN50 – 200
- Push cable with a diameter of 7.6 mm

HD Box

- Touch control panel with integrated PC and Windows OS
- Resolution 1280 x 800 pix, diagonal 12", high brightness 1000 cd/m², touch control
- USB 2.0/ USB 3.0, WIFI connectivity, light weight and practical ergonomics, dimensions 397 x 280 x 57 mm
- Equipped with DigiCan Light software, can also be supplied with DigiCan PRO with the possibility of creating inspection reports (option)

Axial camera head HD46

- For monitoring DN 50 – 200 mm
- Resolution 1920 x 1080 pix
- Full HD image
- pressure-tight camera head
- integrated probe 33kHz
- pressure sensor

Rotary camera head HD60

- For monitoring DN 65 – 200 mm
- Resolution 1920 x 1080 pix
- Full HD image
- pressure-tight camera head
- integrated probe 33kHz
- pressure sensor
- rotation without antenna from – 105° to +105°
with antenna from –60° to +60°

