



HYDROJET

Hydrojet belongs to one of the most used high-pressure machines. It is popular primarily because of the relation price / power and easy built-in into the common vans. You can choose from wide range of the drive units, high-pressure pumps and accessories. The machine is designed for pipe cleaning DN 50 – 300 mm and in standard is equipped with water tank 2x400 L. We will gladly help you with choice of most suitable configuration for your business.

Basic technical specification:

- Petrol or diesel engine, 18 HP up to 25 HP
- High-pressure pump Speck or Pratissoli
- Basic volume of water tank – 800 L
- Filling of the water tank via „C” flange
- High-pressure hose 3/8" – 1/2" according to option, length 60 m (3/8") or 80 m (1/2")
- Hydraulically controlled high-pressure drum
- Filling hose 3/4" – length 50 m
- Weight 440 – 575 kg – according to chosen option
- Dimension ca. 1360x1408x1300 mm
- Control panel on the front side of the machine
- Emergency stop
- Motohours
- 2x basic jets

Some of optional accessories:

- Radio remote control
- Wide range of jets
- Winding/unwinding of high-pressure hose via cross spindle system and automatic adjustment via integrated hose guiding system
- Pulse system
- Heat insulation of the load room
- Load room covered with a sheet
- Protection against dry-drive (pump)
- Tank volume 1 000 L
- Fix / magnetic working light
- Second high-pressure hose instead of filling hose

IBOS a.s.
Hlínská 694/2b, 370 01 České Budějovice, Czech Republic
Tel.: +420 387 310 227, E-mail: ibos@ibos.cz



www.ibos.cz



Some of possible variants:

Type	Hydrojet 30/190 B	Hydrojet 50/150 B	Hydrojet 70/100 B	Hydrojet 60/120 B	Hydrojet 60/160 D
Engine	Kohler PRO	Kohler PRO	Kohler PRO	Kohler PRO	Kubota D 1105
Power	18 HP	23 HP	23 HP	23 HP	25 HP
Cooling engine	Ventilator	Ventilator	Ventilator	Ventilator	Heat exchanger
Fuel	Benzin	Benzin	Benzin	Benzin	Diesel
High-pressure pump	Speck 30/190 NP25	Speck 50/150 NP25	Speck 70/100 NP25	Speck 60/120 NP25	Pratissoli KT24
Water tank	800 L	800 L	800 L	800 L	800 L
High-pressure hose	60 m 3/8"	60 m 1/2"	60 m 1/2"	60 m 1/2"	80 m 1/2"
High-pressure hose control	Hydraulically	Hydraulically	Hydraulically	Hydraulically	Hydraulically
Filling hose	50 bm 3/4"	50 bm 3/4"	50 bm 3/4"	50 bm 3/4"	50 bm 3/4"
Filling drum controlling	Manually - handle	Manually - handle	Manually - handle	Manually - handle	Manually - handle
Dimension (WxLxH)	1360x1408x1300	1360x1408x1300	1360x1408x1300	1360x1408x1300	1300x1500x1300
Weight (without water)	cca 440 kg	cca 440 kg	cca 440 kg	cca 440 kg	cca 575 kg

